

PROGRAMMING GUIDE

for

**BARCODE
SCANNERS**

The guide can be used as keyboard emulation, RS- 232C serial interface, and CMOS serial interface and wand emulation.

IMPORTANT NOTICE

This is a general guide for various scanners, and not all functions will perform in every scanner. Other than specified in this guide, for any special functions or specifications, please contact your dealer for details.

Every effort is made to ensure the accuracy of our product information; however, we accept no responsibility for errors or omissions including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. We shall not be liable for errors contained herein or for incidental consequential damages in connection with the furnishing, performance, or use of this material.

Specification or version may be subject to change without notice. The actual specification and version are based on the product delivered.

PRINTED IN DECEMBER 2001

TABLE OF CONTENTS

| | |
|---|----|
| Introduction..... | 1 |
| Default Parameters | 2 |
| Program Procedure..... | 5 |
| System Setting | 6 |
| General Configuration | |
| Scanning Mode Selection..... | 9 |
| Inter- Message Delay | 10 |
| Inter- Character Delay..... | 11 |
| Message/ Block Mode Selection..... | 11 |
| Beeper Tone Selection | 12 |
| Interface Configuration | |
| RS-232C Serial Communication Parameters Setting | |
| Handshaking Protocol..... | 15 |
| ACK/ NAK Response Time Setting..... | 16 |
| Baud Rate | 16 |
| Data Bit | 17 |
| Stop Bit | 17 |
| Parity Setting..... | 17 |
| Message Terminator | 18 |
| Keyboard Emulation Parameters Setting..... | 19 |
| Keyboard Type Selection | 19 |
| Language Selection | 21 |
| Message Terminator | 22 |
| Function Key Emulation | 23 |
| Capital Lock Setting..... | 23 |
| Wand Emulation Parameters Setting | 24 |
| Emulation Data Output Selection..... | 25 |
| Wand Emulation Narrow/Wide Ratio..... | 25 |
| Cursor Pad Work at Numlock | 25 |
| USB Interface Parameters Setting..... | 26 |
| Keyboard Type | 26 |
| Message Terminator | 26 |
| The Symbolologies | |
| Reading Code Selection..... | 28 |
| Code 39 Parameters Setting | 30 |
| Interleaved 2 Of 5 Parameters Setting | 31 |

| | |
|---|----|
| Chinese Post Code Parameters Setting..... | 32 |
| UPC/ EAN/ JAN Parameters Setting | 33 |
| Coda bar/ Monarch Parameters Setting..... | 37 |
| Code 128 Parameters Setting | 37 |
| MATRIX 25 Parameters setting | 38 |
| MSI/Plessy parameters setting..... | 39 |
| Italian Pharmacy Parameters Setting | 40 |
| Barcode Length Setting | 41 |
| ISBN/ ISSN Conversion..... | 42 |
| Data Editing | |
| Header and Trailer..... | 43 |
| Barcode Identifier Code Selection | 44 |
| Barcode Identifier Code Setting..... | 45 |
| Truncate Header/Trailer Character | 47 |
| Appendixes | |
| Appendix A | |
| Code 39 Full ASCII Code Table..... | 49 |
| Appendix B | |
| Code 39 Full ASCII Bar Code Table | 52 |
| Appendix C | |
| Barcode Samples | 62 |
| Appendix D | |
| Quick Settings..... | 63 |

1. INTRODUCTION

Scanning a series of programming bar code labels can configure the series scanners. This allows decoding options and interface protocols to be tailored to a specific application. The configuration is stored in non-volatile memory and will not be lost by removing power from the scanner.

The scanner must be properly powered before programming. For RS-232C type scanners, an external power adapter must be used to supply DC power to the scanner. If a keyboard emulation type scanner is used with an IBM PC/XT/AT, PS/2 or any fully compatible computers, power will be drawn from the keyboard port. No external power adapter is required. If keyboard emulation type scanner is used with any other non IBM PC compatible computers, an external power adapter may be needed.

During the programming mode, the laser scanner will acknowledge a good and valid reading with a short beep. It will give long beeps for either an invalid or bad reading.

2. PROGRAMMING OPTIONS

Programmable options are divided into four groups. The first group includes the options that show the general behavior of the laser scanner. The second group of options governs the operation of RS-232C type serial ports. The third group selects the keyboard type that the keyboard emulation type will be emulated. The last group sets the decoding parameters for each barcode symbology.

3. DEFAULT PARAMETERS

This table gives the default settings of all the programmable parameters. The default settings will be restored whenever the "Reset" programming label is scanned and the laser scanner is in programming mode.

DEFAULT VALUES OF OPERATING PARAMETERS

| Function | Default Values |
|--|----------------|
| Scanning Mode Selection | Trigger mode |
| Header and trailer | None |
| Inter-Message delay | Normal |
| Inter-Character delay | Normal |
| Message/Block mode selection | Message |
| Send command in block mode communication | Disable |
| Good read beeper tone selection | Medium |
| Code identifier transmitting | Disable |

PREDEFINED BARCODE IDENTIFIERS*

| | |
|------------------------------------|----|
| Code 39 barcode identifier code | M |
| ITF 2 of 5 barcode identifier code | I |
| Chinese post code identifier code | H |
| UPC-E barcode identifier code | E |
| UPC-A barcode identifier code | A |
| EAN-13 barcode identifier code | F |
| EAN-8 barcode identifier code | FF |
| Codabar barcode identifier code | N |
| Code 128 barcode identifier code | K |
| Code 93 barcode identifier code | L |
| MSI barcode identifier code | P |
| MATRIX 25 barcode identifier code | G |

DEFAULT VALUES OF KEYBOARD EMULATION PARAMETERS SETTING

| Function | Default Values |
|-------------------------|------------------------|
| Keyboard type selection | IBM PC/AT USA |
| Message terminator | Enter/ carriage Return |

DEFAULT VALUES OF RS-232C SERIAL COMMUNICATION PARAMETERS

| Function | Default Values |
|-------------------------------|----------------|
| Handshaking protocol | None |
| ACK/NAK response time setting | 300 msec |
| Baud rate | 9600 |
| Data bit | 8 |
| Stop bit | 1 |
| Parity | Mark |
| Message terminator selection | CR/LF |

DEFAULT VALUES OF WAND EMULATION PARAMETERS

| Function | Default Values |
|---------------------------|----------------|
| i ° Wand emulation speed | Normal |
| i ° Wand emulation output | Black = High |

Note: For wand emulation, the configuration is only effective for the items with asterisk (i °).

DEFAULT VALUES OF USB EMULATION PARAMETERS


| Function | Default Values |
|------------------------|----------------|
| i ° Keyboard Type | US Keyboard |
| i ° Message Terminator | Enter |

DEFAULT VALUES OF DECODING PARAMETERS

| Function | Code | Default Value |
|-------------------------|------------------------|------------------|
| Reading codes Selection | Code 39 | Enable |
| | ITF 2 of 5 | Enable |
| | Chinese Post Code | Disable |
| | UPC/EAN/JAN | Enable |
| | Coda bar | Enable |
| | i ° MSI | Disable |
| | Code 128 | Enable |
| | Code 93 | Enable |
| | i ° ITAT | Disable |
| | i ° EAN-128 | Disable |
| | i ° MATRIX 25 | Disable |
| i ° Italian Pharmacy | Disable | |
| ISSN/ ISBN | Disable | |
| Code 39 | Codes | Standard |
| | Start/stop characters | Not transmitting |
| | Check digit | Disabled |
| | Concatenation | Off |
| Interleaved 2 of 5 | Length | 6-32 digits |
| | Check digit | Disable |
| Chinese Post Code | Length | 10~16 digits |
| | Check digit | Transmit |
| UPC/EAN/JAN | Format | All |
| | Addendum | Disable |
| | UPC-E=UPC-A | Disabled |
| | UPC-A leading digit | Transmit |
| | UPC-A check digit | Transmit |
| | UPC-E leading digit | Transmit |
| | UPC-E check digit | Transmit |
| Coda bar | Type | Standard |
| | Start/stop characters | A, B, C, D |
| | Length | 6~32 digits |
| Code 128 | FNC 2 append | Disable |
| | Check digit | Disable |
| MSI | Length | Variable |
| | Check digit | Transmit |
| Italian Pharmacy | Transmit "A" Character | Not transmitting |
| MATRIX 25 | Length | Fix 10 digits |
| | Check digit | Disable |

Note: The configuration of the items with asterisk (i °) is effective when being appointed in advance.

4. PROGRAM PROCEDURE USING BARCODE MENUS





Start of Configuration

SYSTEM SETTING



RESET

- The reading of the "RESET" label turns all the parameters back to default values.
- When you intend to turn your scanner back to default parameter, please scan the "Start of configuration" label first, then scan "RESET" label



ABORT

- The reading of the "ABORT" label discards all the parameters read prior to the "End of configuration".



RS-232C

- The scanner remains in the last interface mode when the scanner is reset. The label below should be scanned if the scanner is configured the first time.



PC/AT



USB

- The reading of the "SHOW VERSION" label will be show firmware version.



WAND EMULATION



SHOW VERSION



End of Configuration



Start of Configuration

SCANNING MODE SELECTION (for laser scanner)

For series laser scanners, there are 3 scanning modes to suit your application requirements.



Trigger Mode

The scanner becomes inactive as soon as the data is transmitted. It must be triggered to become active again.



Pulse Mode

The scanner will light up when press the pulse mode trigger switch once. And, the scanner will turn off for next pressing.

GENERAL CONFIGURATION

SCANNING MODE SELECTION (For CCD scanner)

The scanner becomes inactive as soon as the data is transmitted. It must be triggered to become active again.



Trigger mode

In auto scan mode, the scanner is still active after the data is transmitted, but the successive transmission of the same bar code is not allowed when the trigger switch is pressed again.




Auto scan mode

This scanner will light up when press the scanner trigger switch once. And, the scanner will turn off for next pressing.



Alternate mode

This mode is similar to Auto scan mode, but double reading for the same barcode is prohibited if the scanner switch is pressed.



Repeat mode



End of Configuration



DATA REDUNDANT CHECK

The option allows you to set decoder data redundant check.



Enable



Disable

INTER-MESSAGE DELAY

These series of scanners allow you to add a delay between two consecutive messages. This delay will be added before each data transmission.



None



100 msec



500 msec



1 Second

INTER-CHARACTER DELAY

This option governs delay time between consecutive characters. Scanning the following labels can alter the delay time.



None



10 msec



20 msec



50 msec

MESSAGE/BLOCK MODE SELECTION

This option allows you to treat scanned data as either an independent message or a block message. In the message mode, the data scanned will be transmitted immediately. In block mode, the data scanned will be appended to the message buffer if the scanner is programmed in block mode. A block of message will only be transmitted after a "Send" command is entered. This mode is only available when the scanner is working with code 39 labels. You are free to choose any character as the "Send" command.



Message



Block





Start of Configuration

SEND COMMAND IN BLOCK MODE COMMUNICATION

You can use this option to set your own "Send" command used in block mode communication.



Enable



Disable



Store



Set

GOOD READ BEEPER TONE SELECTION

You can use this option to set frequency and / or duration of the buzzer after successful reading.



Medium



Low



High



Disable

SOUND DURATION




long(120 ms)



Medium(50 ms)



Short(20 ms)



Very short(5 ms)

*For Alpha-70 and SC-2070 Series only Medium and disable setting available, it's hardware beeper control.



End of Configuration

INTERFACE CONFIGURATION



Start of Configuration

1. RS-232C SERIAL COMMUNICATION PARAMETERS SETTING

The RS-232C scanner supports four handshaking protocols. With these options of communication protocol, you can tailor the scanner to meet the requirement of most systems

HANDSHAKING PROTOCOL



None



RTS/CTS



ACK/NAK



Xon/Xoff

ACK/NAK RESPONSE TIME SETTING



300 msec



2 sec



500 msec



End of Configuration



Start of Configuration

ACK/NAK RESPONSE TIME SETTING (Cont'd)



3 sec



1 sec



5 sec

BAUD RATE



19200



9600



4800



2400



1200



600

DATA BIT



7



8

STOP BIT



1



2

PARITY



Even



Odd



Mark



Space



None



End of Configuration



Start of Configuration

MESSAGE TERMINATOR (FOR RS-232C TYPE ONLY)



None



CR/LF



CR



LF



H Tab



STX/ETX



EOT

2. KEYBOARD EMULATION PARAMETERS SETTING

KEYBOARD TYPE SELECTION

The keyboard emulation scanners can emulate a number of personal computers keyboard and a number of terminal keyboard. Keyboard emulation is activated whenever you have selected the type of keyboard for which the scanner is going to emulate. Choose the appropriate type of keyboard emulation by scanning the labels under the following labels.



IBM AT



PS/2 30-80



IBM 5550



IBM 5295 Terminal



IBM XT



IBM 5530-SC



IBM 5530-ZC




End of Configuration



Start of Configuration

KEYBOARD TYPE SELECTION (Cont' d)



NEC 9801



IBM 3196 Terminal



APPLE MAC II(i) }



IBM 3477/3472 Terminal



PS2/30/56



IBM 3477 Terminal
(Without break code)



NEC 5200(i) }

Note: The configuration of the items with asterisk (}) is optional.

KEYBOARD LANGUAGE SELECTION



USA



UK



French



Spanish



Italian



Swiss



Swedish



End of Configuration



MESSAGE TERMINATOR (FOR KEYBOARD WEDGE USE)



None



Return / Enter



Hor. TAB



Execute

KEYBOARD TYPE SELECTION



Scan Code Mode



Alt mode

BREAK CODE ON/ OFF SETTING (FOR IBM Terminals 31xx, 34xx, 37xx USE)

To select the interface for these IBM terminals, read the correct key transmission code.



ON



OFF

FUNCTION KEY ACTIVE ON/ OFF (FOR IBM AT USE)

Function keys can be concatenated with input data as header and/or trailer. See table on page 40.



ON



OFF

CAPITAL LOCK ON/ OFF

Select the suitable code to match your keyboard caps lock status.



ON



OFF

Function key emulation (only for PC/AT)

Numlock on/off



OFF



ON



End of Configuration



Start of Configuration

00H~1FH ASCII Code defined



Alt-mode code



Ctrl+code

3. WAND EMULATION PARAMETERS SETTING

EMULATION SPEED SELECTION



Low



Medium



Normal



High



Higher

EMULATION DATA OUTPUT SELECTION

The decoded data output logic level can be set to befit the external decoder.



Black = High



Black = Low

WAND EMULATION NARROW/WIDE RATIO



1:2



1:3

CURSOR PAD WORK AT NUMLOCK



ON



OFF



End of Configuration




Start of Configuration


4. USB INTERFACE PARAMETERS SETTING

The USB mode is effectively a keyboard emulator that works with hosts that USB-compatible operating system and USB ports. USB compatible operating systems are Windows 98, Windows NT 5.0 and later, no additional software is needed since the USB driver support is built into this operating system.

KEYBOARD TYPE




US Keyboard



International Keyboard

MESSAGE TERMINATOR



End of Configuration

THE SYMBOLOGIES



Start of Configuration

READING CODE SELECTION



Code 39 Enable



Code 39 Disable



Coda bar Enable



Coda bar Disable



UPC/ EAN/ JAN Enable



UPC/ EAN/ JAN Disable



ITF 2 of 5 Enable



ITF 2 of 5 Disable



Chinese Post Code Enable



Chinese Post Code Disable



Code 128 Enable



Code 128 Disable



MSI Enable



MSI Disable



Code 93 Enable



Code 93 Disable



IATA Enable



IATA Disable



EAN-128 Enable



EAN-128 Disable



MATRIX 25 Enable



MATRIX Disable



End of Configuration



Start of Configuration

READING CODE SELECTION (Cont' d)



Italian Pharmacy Enable



Italian Pharmacy Disable

CODE 39 PARAMETERS SETTING

CHARACTER SET



Standard Code 39



Full ASCII Code 39

START/STOP CHARACTER TRANSMISSION



Yes



No

CHECK DIGIT



Calculate and Transmit



Calculate but not Transmit



NO

CONCATENATION



Enable




Disable

INTERLEAVED 2 OF 5 PARAMENTERS SETTING

Examples: Felting length 4 to 8 digits

LENTGTH




MAX



Min



Set



End of Configuration



Start of Configuration

CHECK DIGIT



NO



Calculate and Transmit



Calculate but not Transmit

CHINESE POST CODE PARAMETERS SETTING

LENGTH




MAX



MIN



Set



CHECK DIGIT



NO



Calculate and Transmit



Calculate but not Transmit

UPC/EAN/JAN PARAMETERS SETTING

FORMAT



All



EAN-8 or EAN-13



UPC-A and EAN-13



UPC-A and UPC-E



UPC-A



UPC-E



End of Configuration




Start of Configuration

UPC/EAN/JAN PARAMETERS SETTING (Cont' d)



EAN-13



EAN-8

ADDENDUM



NO



5 Characters



2 Characters



2 or 5 Characters

FORCE UPC-E TO UPC-A FORMAT



Yes



No

FORCE UPC-A TO EAN-13 FORMAT



Yes



No

TRANSMIT UPC-A LEADING CHARACTER



Yes



No

TRANSMIT UPC-A CHECK DIGIT



Yes



No

TRANSMIT UPC-E LEADING CHARACTER



Yes



No



End of Configuration



Start of Configuration

TRANSMIT UPC-E CHECK DIGIT



Yes



No

TRANSMIT EAN-13 CHECK DIGIT



Yes



No

TRANSMIT EAN-8 CHECK DIGIT



Yes



No

CODABAR/ MONARCH PARAMETERS SETTING

START/ STOP CHARACTER TRANSMISSION



No



A, B, C, D



DC1-DC4



a/ t, b/ n, c/ *, d/ e

CONCATENATION



Enable



Disable

CODE 128 PARAMETERS SETTING

FNC 2 CONCATENATION



Enable



Disable



End of Configuration



Start of Configuration

CODE 128 PARAMETERS SETTING (Cont' d)

CHECK DIGIT



No



Calculate but not Transmit



Calculate and Transmit

UCC/EAN128 PARAMETERS SETTING

The character FNC1 can be transmitted or not using these codes.



FNC1 Character Transmitted



FNC1 not Transmitted

MATRIX 25 PARAMETERS SETTING

Examples: Felting length 4 to 8 characters




MAX



MIN



Set



MSI/PLESSY PARAMETERS SETTING

Examples: Felting length 4 to 8 characters




MAX



MIN



SET



Double Check digit



Calculate but not Transmitted




No



Calculate but only first one Transmitted



Calculated and both Transmitted




Single Check digit



Calculated but not Transmitted



Calculated and transmitted



End of Configuration



Start of Configuration

MSI/PLESSY PARAMETERS SETTING (Cont' d)

PLESSY CODE SETTING



Calculated and transmitted



Calculate but not transmitted

CHECK DIGIT



No



Calculate and Transmit



Calculate but not Transmit

ITALIAN PHARMACY PARAMETERS SETTING

TRANSMIT "A" CHARACTER



Yes



No

BARCODE LENGTH SETTING

CODE 39 LENGTH SETTING



MAX



MIN

CODE 93 LENGTH SETTING



MAX



MIN

CODE 128 LENGTH SETTING



MAX



MIN

CODABAR LENGTH SETTING




MAX



MIN



SET



End of Configuration



Start of Configuration

ISBN/ ISSN CONVERSION

The function converts the UPC/EAN codes appearing on books and magazine not ISBN/ISSN format.



ACTIVE ISBN/ ISSN



INACTIVE ISBN/ ISSN

DATA EDITING



End of Configuration



Start of Configuration

HEADER AND TRAILER

This option allows you to append a header and/or a trailer to every message transmitted via the serial ports or the keyboard port. There is no restriction in selecting header or trailer characters as far as the sum of the lengths of header and trailer is not greater than 10 digits.



Header



Trailer



Set

1. Select either header or trailer you are going to program by scanning the corresponding label
2. Scan the character(s) you want from the enclosed ASCII table to set as header or trailer (be sure to enable full ASCII code 39 option before you start).
3. Read the "Set" label to set your choice into memory.

BARCODE IDENTIFIER CODE SELECTION

The series of scanners can transmit max.2-digit barcode identifier code for different types of barcodes. Use the labels to choose transmit or not transmit predefined barcode identifier code (ID's are listed on page 2):



Enable



Disable

BARCODE IDENTIFIER CODE SETTING

Each of the series type scanners can set max.2 digits as barcode identifier code according to different barcode. The procedure is as follows:

1. Scan "Start of configuration" label
2. Scan "Barcode identifier setting code" label.
3. Scan the new code mark from ASCII table (max. two digits). For example, if one "AB" want for code mark then scan "A" and "B".
4. Scan "Set" label.
5. Scan "End of configuration" label.



UPC-E



UPC-A



EAN-13



EAN-8



Chinese post code



ITF 2 OF 5



End of Configuration



BARCODE IDENTIFIER CODE SETTING (Cont' d)



Coda bar



Code 39



Code 128



Code 93



MSI



MATRIX 25



Set

Truncate Header/Trailer Character
(Version az1.24, dz1.05, ac1.01, dz1.05,p11.39 Or higher is required)

You can truncate a number header or trailer for a symbology. When you do, the specific character you select is deleted from the symbology you want.



Truncate header character



Truncate trailer character



set

4. Scan "set" barcode
5. end of configuration

- 1.scan "start of configuration"
- 2.select "truncate header or truncate trailer"
- 3.scan two barcode value from the full ASCII code table(0~9) For example, if 2 number header you want clear then scan "0" and "2"



APPENDIX A

CODE 39 FULL ASCII CODE TABLE

APPENDIXES

| ASCII | CODE 39 | VALEUR HEXA. | ASCII | CODE 39 | VALEUR HEXA. |
|-------|---------|--------------|-------|---------|--------------|
| NUL | %U | 00 | % | /E | 25 |
| SOH | \$A | 01 | & | /F | 26 |
| STX | \$B | 02 | ' | /G | 27 |
| ETX | \$C | 03 | (| /H | 28 |
| EOT | \$D | 04 |) | /I | 29 |
| ENQ | \$E | 05 | * | /J | 2A |
| ACK | \$F | 06 | + | /K | 2B |
| BEL | \$G | 07 | , | /L | 2C |
| BS | \$H | 08 | - | - | 2D |
| HT | \$I | 09 | . | . | 2E |
| LF | \$J | 0A | / | / | 2F |
| VT | \$K | 0B | 0 | 0 | 30 |
| FF | \$L | 0C | 1 | 1 | 31 |
| CR | \$M | 0D | 2 | 2 | 32 |
| SO | \$N | 0E | 3 | 3 | 33 |
| SI | \$O | 0F | 4 | 4 | 34 |
| DLE | \$P | 10 | 5 | 5 | 35 |
| DC1 | \$Q | 11 | 6 | 6 | 36 |
| DC2 | \$R | 12 | 7 | 7 | 37 |
| DC3 | \$S | 13 | 8 | 8 | 38 |
| DC4 | \$T | 14 | 9 | 9 | 39 |
| NAK | \$U | 15 | : | /Z | 3A |
| SYN | \$V | 16 | ; | %F | 3B |
| ETB | \$W | 17 | < | %G | 3C |
| CAN | \$X | 18 | = | %H | 3D |
| EM | \$Y | 19 | > | %I | 3E |
| SUB | \$Z | 1A | ? | %J | 3F |
| ESC | %A | 1B | @ | %V | 40 |
| FS | %B | 1C | A | A | 41 |
| GS | %C | 1D | B | B | 42 |
| RS | %D | 1E | C | C | 43 |
| US | %E | 1F | D | D | 44 |
| SP | SP | 20 | E | E | 45 |
| ! | /A | 21 | F | F | 46 |
| " | /B | 22 | G | G | 47 |
| # | /C | 23 | H | H | 48 |
| \$ | /D | 24 | I | I | 49 |

APPENDIX A
CODE 39 FULL ASCII CODE TABLE

| ASCII | CODE 39 | VALEUR HEXA. | ASCII | CODE 39 | VALEUR HEXA. |
|-------|---------|--------------|-------|---------|--------------|
| J | J | 4A | e | +E | 65 |
| K | K | 4B | f | +F | 66 |
| L | L | 4C | g | +G | 67 |
| M | M | 4D | h | +H | 68 |
| N | N | 4E | i | +I | 69 |
| O | O | 4F | j | +J | 6A |
| P | P | 50 | k | +K | 6B |
| Q | Q | 51 | l | +L | 6C |
| R | R | 52 | m | +M | 6D |
| S | S | 53 | n | +N | 6E |
| T | T | 54 | o | +O | 6F |
| U | U | 55 | p | +P | 70 |
| V | V | 56 | q | +Q | 71 |
| W | W | 57 | r | +R | 72 |
| X | X | 58 | s | +S | 73 |
| Y | Y | 59 | t | +T | 74 |
| Z | Z | 5A | u | +U | 75 |
| [| %K | 5B | v | +V | 76 |
| \ | %L | 5C | w | +W | 77 |
|] | %M | 5D | x | +X | 78 |
| ^ | %N | 5E | y | +Y | 79 |
| _ | %O | 5F | z | +Z | 7A |
| ` | %W | 60 | { | %P | 7B |
| a | +A | 61 | | %Q | 7C |
| b | +B | 62 | } | %R | 7D |
| c | +C | 63 | ~ | %S | 7E |
| d | +D | 64 | DEL | %T | 7F |

APPENDIX A
FUNCTION KEY EMULATION

| FUNCTION KEY | ASCII | CODE 39 | FUNCTION KEY | ASCII | CODE 39 |
|--------------|-------|---------|--------------|-------|---------|
| Ins | \$A | 01 | F1 | \$Q | 11 |
| Del | \$B | 02 | F2 | \$R | 12 |
| Home | \$C | 03 | F3 | \$S | 13 |
| End | \$D | 04 | F4 | \$T | 14 |
| Up | \$E | 05 | F5 | \$U | 15 |
| Down | \$F | 06 | F6 | \$V | 16 |
| Left | \$G | 07 | F7 | \$W | 17 |
| Backspace | \$H | 08 | F8 | \$X | 18 |
| TAB | \$I | 09 | F9 | \$Y | 19 |
| Enter(num) | \$J | 0A | F10 | \$Z | 1A |
| Right | \$K | 0B | F11 | %A | 1B |
| PgUp | \$L | 0C | F12 | %B | 1C |
| Enter | \$M | 0D | ESC | %C | 1D |
| PgDn | \$N | 0E | Ctl(L) | %D | 1E |
| shift | \$O | 0F | Alt(L) | %E | 1F |
| 5 (num) | \$P | 10 | | | |

APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE


Start of Configuration


NUL


ENQ
(Up)


SOH
(Ins)


ACK
(Down)


STX
(Del)


BEL
(Left)


ETX
(Home)


BS
(Backspace)


EOT
(End)


HT
(TAB)

APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE


LF
(Enter)(num)


DLE
5 (num)


VT
(Right)


DC1
(F1)


FF
(PgUp)


DC2
(F2)


CR
(Enter)


DC3
(F3)


SO
(PgDn)


DC4
(F4)

















SI
shift(L)


NAK
(F5)


End of Configuration
















APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE

| | |
|---|---|
|  | |
| Start of Configuration | |
|  |  |
| SYN (F6) | GS (ESC) |
|  |  |
| ETB (F7) | RS Ctl (L) |
|  |  |
| CAN (F8) | US Alt (L) |
|  |  |
| EM (F9) | SP |
|  |  |
| SUB (F10) | ! |
|  |  |
| ESC (F11) | " |
|  |  |
| FS (F12) | # |

APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE

| | |
|--|---|
|  |  |
| \$ | + |
|  |  |
| % | , |
|  |  |
| & | - |
|  |  |
| . | . |
|  |  |
| (| / |
|  |  |
|) | 0 |
|  |  |
| * | 1 |
| |  |
| | End of Configuration |

APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE

| | |
|------------------------|---|
| | |
| Start of Configuration | |
| | |
| 2 | : |
| | |
| 3 | ; |
| | |
| 4 | < |
| | |
| 5 | = |
| | |
| 6 | > |
| | |
| 7 | ? |
| | |
| 8 | @ |
| | |
| 9 | A |













APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE

| | |
|---|----------------------|
| | |
| B | I |
| | |
| C | J |
| | |
| D | K |
| | |
| E | L |
| | |
| F | M |
| | |
| G | N |
| | |
| H | O |
| | |
| | End of Configuration |
















APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE

| | |
|--|--|
|  | |
| Start of Configuration | |
| <hr/> | |
|  P |  W |
|  Q |  X |
|  R |  Y |
|  S |  Z |
|  T | [|
|  U | \ |
|  V |] |

APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE

| | |
|---|--|
|  ^ |  e |
|  _ |  f |
|  ` |  g |
|  a |  h |
|  b |  i |
|  c |  j |
|  d |  k |
| <hr/> | |
|  | |
| End of Configuration | |

APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE



Start of Configuration



l



m



n



o



p



q



r



s



t



u



v



w



x



y

APPENDIX B

CODE 39 FULL ASCII BARCODE TABLE



z



{



|



}



~



DEL



End of Configuration

APPENDIX C

BARCODE SAMPLES

Code 39



Code 128



Interleaved 2 of 5



Coda bar(NW-7)



UPC A



EAN-13



APPENDIX D

QUICK SETTINGS

1. Quick Settings for Keyboard Wedge Mode



Program



Reset



PC/AT



End

2. Quick Settings for RS 232 Mode



Program



Reset



RS-232C



End

3. Quick Settings for German Language Keyboard



Program



German Keyboard



End